

Обзор расходных деталей

HiFocus 280i

#A

FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Конструкционная сталь - 1.0330 St12

HiFocus

PG (O2)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
0,5 - 1,5	20	G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2006Y .11.848.221.406	G3004 .11.848.201.1604	G4015 .11.848.201.1515	G501 .11.848.201.081
1 - 3	35				G2007Y .11.848.221.407		G4020 .11.848.201.1520	

HiFocus 280i

#B

FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Конструкционная сталь - 1.0037 St37

HiFocus

PG (O2)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
4 - 6	35	G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2007Y .11.848.221.407	G3004 .11.848.201.1604	G4020 .11.848.201.1520	G501 .11.848.201.081

HiFocus+

PG (O2)

								
4 - 10	60	G901Y .11.848.201.142	G002Y .11.848.221.300	G102 .11.848.221.146	G2008Y .11.848.221.408	G3028 .11.848.201.1628	G4020 .11.848.201.1520	G501 .11.848.201.081
5 - 8	90				G2010Y .11.848.221.410		G4030 .11.848.201.1530	
10 - 15								
6 - 8	130				G2012Y .11.848.221.412		G4030 .11.848.201.1530	
10 - 20								
12 - 25	160				G2017Y .11.848.221.417			
12 - 30		200						
								
6 - 35	280	G931Y .11.848.401.142	G032Y .11.848.421.310	G121 .11.848.421.145	G2326Y .11.848.421.426	G3249 .11.848.401.1649	G4350 .11.848.401.1550	G521 .11.848.401.081
40 - 70						G3219 .11.848.401.1619		

HiFocus CC

PG (O2)

								
4 - 8	60	G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2008Y .11.848.221.408	G3028 .11.848.201.1628	G4020 .11.848.201.1520	G501 .11.848.201.081
4 - 15	90				G2010Y .11.848.221.410		G4030 .11.848.201.1530	
6 - 20	130				G2012Y .11.848.221.412			
12 - 25	160				G2014Y .11.848.221.414			

Обзор расходных деталей

HiFocus 280i

#C

FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Нержавеющая сталь - 1.4301 CrNi

HiFocus+

PG (Ar, H₂)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
15	280					G3229 .11.848.401.1629	G4335 .11.848.401.1535	
20 - 30						G3219 .11.848.401.1619		
40						G3209 .11.848.401.1609	G4340 .11.848.401.1540	
50 - 70							G4345 .11.848.401.1545	
		G971 .11.848.211.142	G071 .11.848.411.500	G125 .11.848.421.149	G2725 .11.848.411.625			G521 .11.848.401.081

HiFinox

PG (N₂/H₂)

								
1 - 5	60						G4022 .11.848.201.1522	
6							G4025 .11.848.201.1525	
		G941 .11.848.211.142	G042 .11.848.211.510	G101 .11.848.221.145	G2010Y .11.848.221.410	G3008 .11.848.201.1608		G501 .11.848.201.081

HiFocus F+

PG (Ar, H₂)

								
6 - 12	130			G105 .11.848.221.149				
15	160			G104 .11.848.221.148				
		G941 .11.848.211.142	G052 .11.848.311.510		G2514 .11.848.311.614	G3018 .11.848.201.1618	G4030 .11.848.201.1530	G501 .11.848.201.081

HiFocus 280i

#D

FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Нержавеющая сталь - 1.4571 CrNiTi

HiFocus+

PG (Ar, H2)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
15 - 25	280	G971 .11.848.411.142	G071 .11.848.411.500	G125 .11.848.421.149	G2725 .11.848.411.625	G3219 .11.848.401.1619	G4340 .11.848.401.1540	G521 .11.848.401.081
30						G3209 .11.848.401.1609		
40							G4345 .11.848.401.1545	

Обзор расходных деталей

HiFocus 280i

#E

FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Алюминий - 3.3535 AlMg3

HiFocus

PG (Air)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
1 - 4	35	G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2007Y .11.848.221.407	G3008 .11.848.201.1608	G4020 .11.848.201.1520	G501 .11.848.201.081

HiFocus+

PG (Ar, H2)

								
12 - 15	280	G971 .11.848.411.142	G071 .11.848.411.500	G125 .11.848.421.149	G2725 .11.848.411.625	G3219 .11.848.401.1619	G4340 .11.848.401.1540	G521 .11.848.401.081
20 - 30						G3209 .11.848.401.1609		
40 - 80						G4345 .11.848.401.1545		

HiFinox

PG (N2/H2)

								
3 - 6	60	G941 .11.848.211.142	G042 .11.848.211.510	G101 .11.848.221.145	G2010Y .11.848.221.410	G3018 .11.848.201.1618	G4022 .11.848.201.1522	G501 .11.848.201.081

HiFocus F

PG (Ar, H2)

								
6 - 15	130	G941 .11.848.211.142	G052 .11.848.311.510	G105 .11.848.221.149	G2514 .11.848.311.614	G3008 .11.848.201.1608	G4030 .11.848.201.1530	G501 .11.848.201.081