

Обзор расходных деталей

HiFocus 280i

#A

FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Конструкционная сталь - 1.0330 St12

HiFocus

PG (O2)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
0,5 - 1,5	20	G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2006Y .11.848.221.406	G3004 .11.848.201.1604	G4015 .11.848.201.1515	G501 .11.848.201.081
1 - 3	35				G2007Y .11.848.221.407		G4020 .11.848.201.1520	

HiFocus 280i

#B








FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Конструкционная сталь - 1.0037 St37















HiFocus

PG (O2)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
4 - 6	35							
		G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2007Y .11.848.221.407	G3004 .11.848.201.1604	G4020 .11.848.201.1520	G501 .11.848.201.081








HiFocus+

PG (O2)

									
4 - 10	60	G901Y .11.848.201.142	G002Y .11.848.221.300	G102 .11.848.221.146	G2008Y .11.848.221.408	G3028 .11.848.201.1628	G4020 .11.848.201.1520	G501 .11.848.201.081	
5 - 8	90				G2010Y .11.848.221.410		G4030 .11.848.201.1530		
10 - 15					130		G2012Y .11.848.221.412		G4025 .11.848.201.1525
6 - 8	160						G2014Y .11.848.221.414		G4030 .11.848.201.1530
10 - 20							200		
12 - 25									
									
6 - 35	280	G931Y .11.848.401.142	G002Y .11.848.421.310	G121 .11.848.421.145	G2326Y .11.848.421.426	G3249 .11.848.401.1649	G4350 .11.848.401.1550	G521 .11.848.401.081	
40 - 70						G3219 .11.848.401.1619			

HiFocus CC

PG (O2)

								
4 - 8	60	G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2008Y .11.848.221.408	G3028 .11.848.201.1628	G4020 .11.848.201.1520	G501 .11.848.201.081
4 - 15	90				G2010Y .11.848.221.410			
6 - 20	130				G2012Y .11.848.221.412			
12 - 25	160				G2014Y .11.848.221.414			

Обзор расходных деталей

HiFocus 280i

#C








FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Нержавеющая сталь - 1.4301 CrNi



HiFocus+

PG (Ar, H2)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
15	280	G971 .11.848.411.142	G071 .11.848.411.500	G125 .11.848.421.149	G2725 .11.848.411.625	G3229 .11.848.401.1629	G4335 .11.848.401.1535	G521 .11.848.401.081
20 - 30						G3219 .11.848.401.1619		
40						G3209 .11.848.401.1609	G4340 .11.848.401.1540	
50 - 70							G4345 .11.848.401.1545	



HiFinox

PG (N2/H2)

								
1 - 5	60	G941 .11.848.211.142	G042 .11.848.211.510	G101 .11.848.221.145	G2010Y .11.848.221.410	G3008 .11.848.201.1608	G4022 .11.848.201.1522	G501 .11.848.201.081
6							G4025 .11.848.201.1525	

HiFocus F+

PG (Ar, H2)

								
6 - 12	130	G941 .11.848.211.142	G052 .11.848.311.510	G105 .11.848.221.149	G2514 .11.848.311.614	G3018 .11.848.201.1618	G4030 .11.848.201.1530	G501 .11.848.201.081
15	160			G104 .11.848.221.148				

HiFocus 280i

#D








FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Нержавеющая сталь - 1.4571 CrNiTi

HiFocus+

PG (Ar, H2)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
								
15 - 25	280	G971 .11.848.411.142	G071 .11.848.411.500	G125 .11.848.421.149	G2725 .11.848.411.625	G3219 .11.848.401.1619	G4340 .11.848.401.1540	G521 .11.848.401.081
30						G3209 .11.848.401.1609		
40						G4345 .11.848.401.1545		

Обзор расходных деталей

HiFocus 280i

#E

FlowControl 3 - PerCut 440 / 450

Версия данных: 6 - Действительно с: 15.07.2011

Алюминий - 3.3535 AlMg3

HiFocus

PG (Air)

Толщина [mm]	Сила тока резки [A]	Трубка охлаждения	Катод	Газовод	Сопло	Наконечник сопла	Наконечник для сопла вихревого газа	Защитный колпачок
1 - 4	35							
		G901Y .11.848.201.142	G002Y .11.848.221.300	G101 .11.848.221.145	G2007Y .11.848.221.407	G3008 .11.848.201.1608	G4020 .11.848.201.1520	G501 .11.848.201.081

HiFocus+

PG (Ar, H2)

								
12 - 15	280	G971 .11.848.411.142	G071 .11.848.411.500	G125 .11.848.421.149	G2725 .11.848.411.625	G3219 .11.848.401.1619	G4340 .11.848.401.1540	G521 .11.848.401.081
20 - 30						G3209 .11.848.401.1609		
40 - 80						G4345 .11.848.401.1545		

HiFinox

PG (N2/H2)

								
3 - 6	60	G941 .11.848.211.142	G042 .11.848.211.510	G101 .11.848.221.145	G2010Y .11.848.221.410	G3018 .11.848.201.1618	G4022 .11.848.201.1522	G501 .11.848.201.081

HiFocus F

PG (Ar, H2)

								
6 - 15	130	G941 .11.848.211.142	G052 .11.848.311.510	G105 .11.848.221.149	G2514 .11.848.311.614	G3008 .11.848.201.1608	G4030 .11.848.201.1530	G501 .11.848.201.081